



TerraWave Solutions® TWS-400 Coaxial Cable

TerraWave's **TWS-400** series cable is designed for easy installation with maximum flexibility where curves, bends and twists rule out the use of standard hard-line transmission cables. The cable is constructed of a UV resistant polyethylene jacket providing maximum durability and protection from harsh elements and is designed for any application requiring high-quality, flexible cabling such as WLL, GPS, WLAN, WISP, WiMax, SCADA and mobile applications. TerraWave's cable is compatible with a wide variety of connectors and is ideal for any off-the-shelf or customized cable assembly. Visit www.terrawave.com for additional information.



TESSCO SKU: 380348
TerraWave Part Number: TWS-400

Construction Specification		
	Material	Diameter
Inner Conductor	Copper Clad Aluminum	0.108" ± 0.001"
Dielectric	Physical Foam Polyethylene	0.285" ± 0.005"
Outer Conductor	Bonded Aluminum Foil + Tinned Copper Braid	Nominal 0.320"
Jacket	Black Polyethylene	0.40" ± 0.008"

Electrical Characteristics	
Capacitance	23.9 pF/ft
Impedance	50 Ω
Inductance	.060 μH/ft
Velocity	85%
Inner Conductor DC Resistance	< 1.39 (Ω/1000 ft)
Outer Conductor DC Resistance	< 1.65 (Ω/1000 ft)
Shielding Effectiveness	> 90 dB
Jacket Spark	5000 VAC
Cut off Frequency	16.2 GHz
Peak Power	16 kW

Mechanical and Environmental Characteristics	
Min. Bend Radius	2.008"
Storage Temperature	-70° F to +185° F
Installation Temperature	-40° F to +185° F
Operating Temperature	-40° F to +185° F

General Information	
Warranty	7 Years
Life Expectancy	20 Years for Outdoor Use



Attenuation and Avg. Power (68° F)			
Frequency MHz	Typical Attenuation dB/100 ft	Max Attenuation dB/100 ft	Average Power kW
30	0.7	0.86	2.91
50	0.9	1.05	2.21
150	1.5	1.7	1.28
220	1.9	2.1	1.05
450	2.7	3	0.72
900	3.9	4.5	0.5
1500	5.1	5.8	0.38
1800	5.7	6.1	0.34
2000	6	6.5	0.33
2500	6.8	7.7	0.29
5800	10.8	12.2	0.18

For detailed product information and to purchase product, please contact a TerraWave wireless networking solutions sales engineer at 210-375-8482, 800-851-4965, sales@terrawave.com or visit www.terrawave.com.

Version: 2.5

**TerraWave Solutions® TWS-400 Coaxial Cable (continued)
Connectors for TWS-400 Series Cable**



**TWS-400 Series
RPTNC Bulkhead Jack (F)**



**TWS-400 Series
TNC Plug (M)**



**TWS-400 Series
N-Style Plug (M)**

TESSCO SKU	TerraWave Part Number	Description
440939	CON-01-400	RPTNC Jack (F)
416952	CON-02-400	RPTNC Plug (M)
452950	CON-03-400	RPTNC BH Jack (F)
493911	CON-04-400	TNC Jack (F)
415903	CON-05-400	TNC Plug (M)
422933	CON-06-400	N-Style Jack (F)
462958	CON-07-400	N-Style Plug (M)
436949	CON-07-400-RA	RA N-Style Plug (M)
483983	CON-08-400	N-Style BH Jack (F)
452992	CON-09-400	RP N-Style Jack (F)

TESSCO SKU	TerraWave Part Number	Description
498921	CON-10-400	RP N-Style Plug (M)
488953	CON-11-400	BNC Jack (F)
443916	CON-12-400	BNC Plug (M)
499992	CON-13-400	RPBNC Jack (F)
466931	CON-14-400	RPBNC Plug (M)
430910	CON-15-400	RPBNC BH Jack (F)
479910	CON-17-400	SMA Jack (F)
451992	CON-18-400	SMA Plug (M)
432923	CON-19-400	RPSMA Jack (F)
464918	CON-20-400	RPSMA Plug (M)

Crimping and Stripping Tools for TWS-400 Series Cable

SKU	TerraWave Part Number	Product Description
316485	HT-106L	Crimp Tool
449946	HT-322C1	2-Blade Strip Tool
435904	HT-322S3	3-Blade Strip Tool
372317	TWS-CTK-400	3-Blade Strip and Crimp Tool Kit



**TWS-400 Series
HT-106L Crimp Tool**



**TWS-400 Series
HT-22S3 3-Blade Strip Tool**

Connector Adapters for TWS-400 Connectors

SKU	TerraWave Part Number	Product Description
323264	RARPTNCJ-RPTNCP	RA RPTNC Jack (F) to RPTNC Plug (M)
467986	RPTNCJACK-NPLUG	RPTNC Jack (F) to N-Style Plug (M)
413999	RPTNCP-NJ	RPTNC Plug (M) to N-Style Jack (F)
424971	RPTNCP-NP	RPTNC Plug (M) to N-Style Plug (M)
315485	RPTNCP-RPSMAJ	RPTNC Plug (M) to RPSMA Jack (F)
424995	NJACK-NJACK	N-Style Jack (F) to N-Style Jack (F)
485981	NM-NM	N-Style Plug (M) to N-Style Plug (M)
312060	SMAP-TNCJ	SMA Plug (M) to TNC Jack (F)
437905	AXA-SMSM	SMA Jack (F) to SMA Jack (F)



**N-Style Plug (M)
to N-Style Plug (M)**



**RA RPTNC Jack (F)
to RPTNC Plug (M)**

For detailed product information and to purchase product, please contact a TerraWave wireless networking solutions sales engineer at 210-375-8482, 800-851-4965, sales@terrawave.com or visit www.terrawave.com.

