



REVISION		
ISS	ZONE	DESCRIPTION

Recmmended Stripping Dimensions

- NOTE:
- 1.Impedance: 50Ω
  - 2.Frequency Range: DC 0-18 GHz
  - 3.V.S.W.R.: 1.3 MAX.@ 6GHz
  - 4.Voltage Rating: 500V rms
  - 5.Contact Resistance: Center Contacts: 2.0 mΩ Max  
Outer Contacts: 2.0 mΩ Max
  - 6.Insulation Resistance : 5000 MΩ MIN.
  - 7.Interface in Accordance With: MIL-STD-348A
  - 8.Operating Temperature Range:-65°~165°C
  - 9.ROHS Compliance.

TOLERANCES			
DIMENSIONS ARE IN MILLIMETER			
UNLESS OTHERWISE SPECIFIED			
.X	±0.2		
.XX	±0.1		
.XXX	±0.05		
ANGLES	±5°		

TITLE	SMA Bulkhead Jack for TWS-200 Cable
PART NO.	CON-23-200
DRAWN NO.	
FILE PATH:	

TerraWave Solutions	
APPROVED	DATE
CHECKED	DATE
DRAWN	DATE

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWN NO.
7	FERRULE	BRASS	GOLD	1	M-0046
6	PIN	Be Cu	GOLD	1	C-0423
5	BODY	BRASS	GOLD	1	B-0219
4	INSULATOR A	TEFLON	NONE	1	T-0263
3	WASHER	BRASS	GOLD	1	F-0023
2	WASHER	BRASS	GOLD	1	G-0017
1	NUT	BRASS	GOLD	1	D-0008